

Data sheet

ID	AKG
Description	distribution box
Colour	white, similar to RAL 9010
Classification	AC 400 V



Norms: ÖVE/ÖNORM EN 60670-1:2014, ÖVE/ÖNORM EN 60670-22:2007



Working temperature	Degree of protection (IP)	UV-Level
-5 to +60 °C	IP30	L2

Art. no.	Dimensions Ø/LxB x T	For tube diameter	Small Package	Large Package
719 719	100 x 100 x 45 mm	-	50 pc	1750 pc
722 722	150 x 150 x 65 mm	-	25 pc	875 pc
724 724	200 x 200 x 70 mm	-	12 pc	288 pc
727 727	400 x 200 x 70 mm	-	5 pc	90 pc
726 726	400 x 400 x 70 mm	-	4 pc	72 pc

Details	
Halogen free	False
Tackable	False
Number of inlets	-
Type of housing feed-through	None
Equipped with	None
Cover model	Mounting cover
Explosion-tested version	True
Weatherproof	False
Material	PVC-U

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.