

Data sheet

ID	ALU RH
Description	dado trunking
Properties	compression resistance >1250 N, halogen-free, plain finishing
Fire Behaviour	non flame propagating



Norms: EN 50085, BS4678 Part 4



Length	Number of covers	Number of partitions	UV-Level
3000 mm	1	1	L3

Art. no.	Width x Depth	Small Package	Large Package
034 190	100 x 65 mm	3 m	-
034 199	130 x 65 mm	3 m	-
034 204	170 x 65 mm	3 m	-

Further technical details

Details

Covers supplied with the product	False
Symmetric	True
Construction type rectangular	True
Halogen free	True
Surface protection	Untreated
Construction rear wall (inner side)	Continuous C-profile
Protection film	False
With duct connector	False
Mounting perforation in base	False
Mounting method covers	Inner lying
With cable fixing clip	False
Material	Al

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.