

Data sheet

ID	FXKVM SW
Description	slip type coupler
Properties	for sandtight connections of FXKVR and FXKVS ductings
Colour	black, similar to RAL 9005
Classification	N 450, IP 40



Norms: ÖVE/ÖNORM EN 61386-1:2009, ÖVE/ÖNORM EN 61386-24:2011



Operating temperature
-30 bis +70 °C

UV-Level
L2

Art. no.	Inner diameter	Outer diameter	Small Package	Large Package
055 202	40 mm		-	-
025 755	50 mm	57,9 mm	100 pc	-
025 756	63 mm	73 mm	60 pc	-
025 757	75 mm	84,2 mm	37 pc	-
025 758	90 mm	100,5 mm	22 pc	-
032 331	125 mm	142,2 mm	25 pc	900 pc
041 351	175 mm	193 mm	-	-
040 801	200 mm	221 mm	10 pc	-

Further technical details

Details

With rubber seal	False
Surface protection	Untreated
Surface polished	False
Material	PE

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.