


# Data sheet

ID	<b>GSR PB</b>
Description	rigid steel conduit, without thread, powder-coated
Properties	very heavy compression resistance, very heavy impact resistance
Fire Behaviour	non flame propagating
Classification	55561



Compressive strength class	Impact strength	Working temperature	UV-Level
Extra heavy (Class 5)	Extra heavy (Class 5)	-45 to +250 °C	L3

Art. no.	Outer diameter	Inner diameter	Small Package	Large Package
080 210	16 mm	13,2 mm	3 m	30 m
019 913	20 mm	16,8 mm	3 m	30 m
019 914	25 mm	21,8 mm	3 m	30 m
019 915	32 mm	28,8 mm	3 m	21 m
019 916	40 mm	36,8 mm	3 m	15 m
019 917	50 mm	46,8 mm	3 m	15 m
019 918	63 mm	59,4 mm	3 m	9 m

## Areas of Recommended Application

Area	
Flush mounted (plaster)	True
Surface mounted	True
Suitable for concrete installation	False
Machine and systems installation	True
Suitable for subsurface installation (screed))	True
Outdoor installation	True
Installation on wood	True
Suitable for hollow wall installation	True
Installation in underground	False

## Further technical details

Details	
Model	Rigid threaded
Surface protection	Lacquered
Material quality	Steel (strip steel rolled)
Material	Stahl

\*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.