


Data sheet

Part No.	HFAFT/MBS BK
Description	adaptor with female thread and male bush, halogen-free for the connection of rigid or pliable conduits with distribution and enclosure boxes
Colour	black, similar to RAL 9005



Working temperature
-25 to +90 °C

Degree of protection (IP)
IP54

Art. no.	Nominal diameter	Thread connection size	Thread length	Total length	ps	pl
009 673	16 mm	M16 x 1.5	11 mm	30 mm	100 pc	2400 pc
009 674	20 mm	M20 x 1.5	14 mm	35 mm	100 pc	1200 pc
009 675	25 mm	M25 x 1.5	14 mm	45 mm	50 pc	600 pc
009 676	32 mm	M32 x 1.5	14 mm	48 mm	20 pc	480 pc
009 677	40 mm	M40 x 1.5	14 mm	52 mm	25 pc	300 pc
009 678	50 mm	M50 x 1.5	16 mm	66 mm	10 pc	120 pc
104 458	63 mm	M63 x 1.5	30 mm	105 mm	8 pc	64 pc

Areas of Recommended Application

Area	
Approved in combination with protective conduit CSA	False
Approved in combination with protective conduit UR	False
Approved in combination with protective conduit DIN EN 61386-23	True
Approved in combination with protective conduit Lloyd's Register	False

Further technical details

Details	
Model	Straight
Revolving thread	False
Construction type	Internal thread
Type of connection	Plug-in connection
Thread type	Metric
Material sealing	No sealing
Material	PC-Blend