

Data sheet

ID	KSB 45
Description	slip type bend, with moulded-on coupler
Properties	for sandthight connections of KSR, BR and UDR ductings in an angle of 45°
Colour	black, similar to RAL 9005
Classification	N 450



Norms: ÖVE/ÖNORM EN 61386-1:2009, ÖVE/ÖNORM EN 61386-24:2011



Angle of bow	Operating temperature	UV-Level
45 °	-5 bis +60 °C	L2

Art. no.	Inner diameter	Outer diameter	Small Package	Large Package
001 836	50 mm	54,3 mm	50 pc	-
001 837	63 mm	68 mm	20 pc	-
001 838	75 mm	80,6 mm	12 pc	-
001 839	90 mm	96,5 mm	3 pc	-
001 840	110 mm	117 mm	-	-
001 841	125 mm	133,1 mm	-	-
001 842	140 mm	149,2 mm	-	-
001 843	160 mm	170 mm	-	-

Further technical details

Details

Surface protection	Untreated
Surface polished	False
Model	Rigid
Shape	Outer - and inner side plain
Material	PVC-U

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.