

Data sheet

Part No.	KSM BK
Description	PVC double slip type coupler for sandtight connections of KSR, BR, KSX and KSXS ductings
Colour	black, similar to RAL 9005
Classification	N 450



Standard: EN 61386-1, EN 61386-24, OVE E 8630



Operating temperature	UV-Level*
-5 bis +60 °C	L2

Art. no.	Inner diameter	Outer diameter	ps	pl
001 930	50 mm	53,7 mm	100 pc	-
001 931	63 mm	67 mm	60 pc	-
001 932	75 mm	79,6 mm	37 pc	-
001 933	90 mm	95,5 mm	22 pc	-
001 934	110 mm	116,3 mm	12 pc	-
001 935	125 mm	132,7 mm	7 pc	-
001 936	140 mm	148,8 mm	6 pc	-
001 937	160 mm	169,5 mm	3 pc	-

Further technical details

Details

With rubber seal	False
Surface protection	Untreated
Surface polished	False
Halogen free	False
Material	PVC-U

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.