


# Data sheet

Part No.	<b>PDD</b>
Description	ceiling slab box, halogen-free  for ceiling panels up to 5.5 cm, allows junction of conduits after embedding in concrete, suitable for ceiling hooks LH 115 and LH 125, with 4 mounting lugs, standard mounting screw spacing 60 mm, exit opening Ø 60 mm, installation height 108 mm, max. 8 conduit entries up to Ø 25 mm and 8 conduit entries up to Ø 20 mm main box part PDDM, fixing Base BFD 60, bottom lid BODL 80
Colour	orange, similar to RAL 2004 blue, similar to RAL 5005



Halogen free  
True

Degree of protection (IP)  
IP30

Art. no.	Dimensions	ps	pl
035 491	Ø 80 x 108 mm	5 pc	50 pc

## Areas of Recommended Application

Area	
break-out opening	True
seal membrane	False
nozzle	False
step membrane	False
Mounting switching equipment	Screwing
Luminaire hook mounting	True
Nozzle	None
With nail lugs	False
Circuit integrity	None

## Further technical details

Details	
Model	Single
Shape	Round
Mounting method	Concrete building
With screws	False
Provided with revolving ring	False
Connectable	False
Equipped with	None
Cover attachment	Snap on
Material	PE