

Data sheet

ID	SCLX-C GR
Description	bracket, halogen free
Properties	for stronger retention of HFXS conduits
Colour	grey, similar to RAL 7001
Fire Behaviour	non flame propagating

halogenfree according to EN 60754



UV-Level
L2

Art. no.	Tube/cable diameter	Small Package	Large Package
043 335	16 mm	100 pc	4000 pc
043 337	20 mm	100 pc	4000 pc
043 339	25 mm	100 pc	4000 pc
043 341	32 mm	100 pc	4000 pc
043 343	40 mm	100 pc	3200 pc
043 345	50 mm	100 pc	2400 pc

Further technical details

Details

Type of fastening	With plug bolt/expanding bolt
Connection type construction part	Clamp
Hinged	False
Surface protection	Untreated
Material	PA-Blend

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.