


# Data sheet

ID	<b>SCLX SW</b>
Description	fixation clip, halogen free
Properties	for mounting with screws with Ø 4mm, for retention and fixture of protective conduits in any position
Colour	black, similar to RAL 9005



Norms: IEC 60754-1, EN 61386-1, EN 61386-23

halogenfree according to EN 60754



UV-Level  
L2

Art. no.	Suitable for pipe diameter	Small Package	Large Package
043 322	16 mm	100 pc	1600 pc
043 324	20 mm	100 pc	1200 pc
043 326	25 mm	100 pc	800 pc
043 328	32 mm	50 pc	600 pc
043 330	40 mm	50 pc	400 pc
043 332	50 mm	50 pc	400 pc

## Further technical details

Details	
Closed	False
Tackable	True
Max. number of tubes	1
Type of fastening	Screw hole
With inlay	False
Material	PA-Blend

\*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.