

# Data sheet

ID	<b>SGM GR</b>
Description	lock nut, halogen-free
Properties	for fixing of conduit glands, with Pg thread
Colour	grey, similar to RAL 7001
Fire Behaviour	non flame propagating



Norms: IEC 60754-1, EN 61386-1, EN 61386-23

halogenfree according to EN 60754



UV-Level

L2

Art. no.	Nominal thread size	Small Package	Large Package
013 673	PG 11	200 pc	5000 pc
013 674	PG 13	200 pc	4000 pc
013 675	PG 16	200 pc	3000 pc
013 676	PG 21	100 pc	2000 pc
016 649	PG 29	30 pc	1500 pc
017 308	PG 36	25 pc	1200 pc
025 198	PG 48	25 pc	800 pc

## Further technical details

### Details

Halogen free	True
Surface protection	Other
Thread type	PG
Glass-fibre reinforced	False
Shock resistant	False
Material	PA-Blend

\*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.