

Data sheet

| | |
|----------------|--|
| ID | SGM SW |
| Description | lock nut, halogen-free |
| Properties | for fixing of conduit glands, with Pg thread |
| Colour | black, similar to RAL 9005 |
| Fire Behaviour | non flame propagating |



Norms: IEC 60754-1, EN61386-1, EN 61386-23

halogenfree according to EN 60754



UV-Level

L2

| Art. no. | Nominal thread size | Small Package | Large Package |
|----------|---------------------|---------------|---------------|
| 043 043 | PG 9 | 200 pc | 5000 pc |
| 043 034 | PG 11 | 200 pc | 5000 pc |
| 043 036 | PG 13 | 200 pc | 4000 pc |
| 043 037 | PG 16 | 200 pc | 3000 pc |
| 026 658 | PG 21 | 100 pc | 2000 pc |
| 043 039 | PG 29 | 30 pc | 1500 pc |
| 043 040 | PG 36 | 25 pc | 1200 pc |
| 043 041 | PG 48 | 25 pc | 800 pc |

Further technical details

Details

| | |
|------------------------|----------|
| Halogen free | True |
| Surface protection | Other |
| Thread type | PG |
| Glass-fibre reinforced | False |
| Shock resistant | False |
| Material | PA-Blend |

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.