

# Data sheet

ID	<b>SH 50/170 WS</b>
Description	cable retainer
Properties	for Starline-trunking SLS/SLC/SLQ
Colour	white, similar to RAL 9010
Fire Behaviour	non flame propagating



UV-Level  
L2

Art. no.	For wall duct depth	Small Package	Large Package
036 063	50 mm	20 pc	800 pc

## Further technical details

Details	
Cover mounting	True
With potential equalization	False
Material	PVC-U

\*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.