

# Data sheet

Part No.	<b>SLN BK</b>
Description	lock nut, halogen-free for fixing of conduit glands, with metric thread according to EN 60423
Colour	black, similar to RAL 9005
Fire Behaviour	non flame propagating



Standard: EN 61386-1, EN 61386-23, EN 60423  
halogenfree according to EN 60754



Working temperature  
-25 to +105 °C

UV-Level\*  
L2

Art. no.	Part No.	Nominal thread size	ps	pl
082 004	SLN 12 BK	M 12	100 pc	-
026 257	SLN 16 BK	M 16	200 pc	8000 pc
026 256	SLN 20 BK	M 20	200 pc	6400 pc
026 255	SLN 25 BK	M 25	100 pc	4000 pc
026 254	SLN 32 BK	M 32	100 pc	2400 pc
026 053	SLN 40 BK	M 40	30 pc	1200 pc
026 054	SLN 50 BK	M 50	25 pc	1000 pc
027 590	SLN 63 BK	M 63	20 pc	480 pc

## Further technical details

### Details

Thread type	Metric
Pitch thread	1,5 mm
Shape	Hexagonal
Halogen free	True
Glass-fibre reinforced	False
Shock resistant	False
Material	PA-Blend

\*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.