

Data sheet

ID	SLS
Description	Starline trunking
Properties	compression resistance >1250 N for the supply of power, data and telecommunication cabling, versatile system in three standard trunking assemblies, all with three fully segregated compartments, further segregation of services possible by using trunking dividers, special clip-on system for robust connections between trunking body and lid (shock- and child-proof).
Colour	white, similar to RAL 9010
Fire Behaviour	non flame propagating



Norms: EN 50085, BS 4678 Part 4



Length	Number of covers	Number of partitions	UV-Level
3000 mm	1	4	L2

Art. no.	Width x Depth	Small Package	Large Package
082 755	170 x 50 mm	3 m	150 m

Further technical details

Details

Covers supplied with the product True	
Symmetric	False
Construction type rectangular	False
Halogen free	False
Surface protection	Untreated
Construction rear wall (inner side)	Continuous C-profile
Protection film	False
With duct connector	False
Mounting perforation in base	False
Mounting method covers	Spanned
With cable fixing clip	False
Material	PVC-U

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.