


Data sheet

Part No.	UPRM Turbo GR
Description	rigid conduit, with sectional corrugation, with moulded-on coupler medium compression resistance, medium impact resistance
Colour	grey, similar to RAL 7037
Fire Behaviour	non flame propagating
Classification	33411
Compression resistance	> 750 N



Standard: EN 61386-1, EN 61386-21



Compressive strength	Impact strength	Operating temperature	Bending strength	UV-Level*
Medium (class 3)	Medium (class 3)	-25 to +60 °C	Rigid	L2

Art. no.	Outer diameter	Inner diameter	VPE small/medium/large
084 201	16 mm	12,5 mm	3 m / 111 m / 6216 m
084 202	20 mm	16,3 mm	3 m / 111 m / 3996 m
084 203	25 mm	21,1 mm	3 m / 57 m / 2622 m
084 204	32 mm	27,4 mm	3 m / 57 m / 1368 m
084 205	40 mm	35,5 mm	3 m / 21 m / 966 m
084 206	50 mm	45,1 mm	3 m / 21 m / 630 m
084 207	63 mm	57,4 mm	3 m / 21 m / 378 m

Areas of Recommended Application

Area	
Flush mounted (plaster)	True
Surface mounted	True
Suitable for concrete installation	True
Machine and systems installation	True
Suitable for subsurface installation (screed))	True
Outdoor installation	False
Suitable for installation on wood	True
Hollow wall	True
Underground installation	True

Further technical details

Details	
Halogen free	False
High conducting inner coating	True
With sleeve	True
Fire retardant version	True
Material	PVC-U

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.