


# Data sheet

ID	<b>VE HG</b>
Description	straight gland
Colour	light grey, similar to RAL 7035
Fire Behaviour	non flame propagating



Working temperature	Degree of protection (IP)	UV-Level
-15 to +60 °C	IP65	L2

Art. no.	Nominal diameter	Thread connection size	Small Package	Large Package
061 216	16 mm	M16 x 1.5	25 pc	-
061 217	20 mm	M20 x 1.5	25 pc	-
061 218	21 mm	PG21	25 pc	-
061 220	29 mm	PG29	10 pc	-

## Areas of Recommended Application

Area	
Approved in combination with protective conduit CSA	False
Approved in combination with protective conduit UR	False
Approved in combination with protective conduit VD TÜV/GGVS	False
Approved in combination with protective conduit DIN EN 61386-23	False
Approved in combination with protective conduit Lloyd's Register	False

## Further technical details

Details	
Model	Straight
Revolving thread	False
Construction type	External thread
Type of connection	Thread
Thread type	Metric
Material sealing	Other
Material	PP

\*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.